



# IVM-CM3 (Confocal and Two-Photon v. 3)

## The New All-in-One Intravital Imaging Platform



### High Contrast and Resolution, Dual-Mode and Tunable Laser

IVM-CM3 is a highly integrated All-in-One Intravital Microscopy system. It possesses the capability to focus on the desired wavelength using its tunable Two-Photon laser unit, covering wavelengths as low as 690 nm, reaching higher up to 1,050 nm, or anywhere in between. The IVM-CM3 seamlessly combines the advantages of both Confocal and Two-Photon Microscopy, offering endless possibilities for three-dimensional imaging of living cells near the skin or deep within tumors in small animals.



### Key Features

- Deep Tissue Imaging with a Tunable Long-Wavelength NIR fs-Laser System
- One-Click Automated Transition between Confocal and Two-Photon Imaging Modes
- Fully Integrated *In Vivo* Maintenance Unit / Animal Stage  
(e.g., Monitoring & Homeostatic Regulation of Animal Vitality)
- Ultra High-Speed Imaging (max. 50 fps - 512 x 512 pixels)
- 4D Animal Motion Compensation (XYZ & Time)


# IVM-CM3 (Confocal and Two-Photon v. 3)

## The New All-in-One Intravital Imaging Platform

### SPECIFICATIONS

Laser	Confocal Laser Unit	• 405 nm (20mW), 488 nm (20mW), 561 nm (20mW), 640 nm (20mW)
	Tunable Two-photon Laser Unit	• Ti: Sapphire laser • Wavelength: 690 - 1050nm, Pulse width < 75 fs, Rep. rate: 80 MHz • Avg. power > 2.5 W, Dispersion compensation: 0 to -43,000 fs <sup>2</sup>
Fluorescence Detector	Confocal Detector	• Wavelength: 450 - 750 nm (DAPI, CFP, GFP, YFP, RFP, Cy5, Cy5.5, etc.) • 4 Ultra-broadband high SNR PMTs (UV to Near IR, Ultra High Sensitivity, Low Dark Current) • Single master pinhole
	Two-photon Detector	• Wavelength: 450 - 750 nm (DAPI, CFP, GFP, YFP, RFP, Cy5, Cy5.5, etc.) • 4 high quantum efficiency PMTs (UV to Near IR, Ultra High Sensitivity, Low Dark Current) • Emission Filter: Individual filter can be mounted on each of four detectors
Scan Head	Scanner	• Polygonal mirror (Fast axis scanning, Max. 66 kHz) • Galvano scanner (Slow axis scanning, Max. 200 μs/step)
Imaging Head	Objectives	• Max. 5 objectives are mountable on IVM Engine Software controlled motorized turret (1X - 100X) • Compatible for commercial objectives
Image	FOV	• 100 x 100 μm <sup>2</sup> - 10 x 10 mm <sup>2</sup>
	Pixel Resolution	• Max. 2,048 x 2,048 pixels
	Imaging Speed	• Standard: 30 fps @ 512 x 512 pixels • (Optional) High Speed: 50 fps @ 512 x 512 pixels
Animal / Sample Stage	Movable Stage	• Travel Range: 50,000 x 50,000 x 75,000 μm (XYZ) • Micromanipulation (Max. 0.2 μm resolution) • 3-axis independent control with Jog Dial & IVM Engine software
	Specimen Holder	• Flexible-design universal <i>in vivo</i> / <i>ex vivo</i> / <i>in vitro</i> specimen holders can be mounted • (Optional) Homeothermic warming system, Holders for window chamber
	Monitoring Camera	• Real-time live animal / sample monitoring
	LED Light	• Installed inside the machine to assist in the observation of live animals or samples
Animal Motion Compensation (Tissue stabilization)	4D <i>In vivo</i> Imaging Motion Compensation	• XY motion compensation: Averaged image acquisition with motion artifact compensation • Z motion compensation: Image-based sample Z position adjustment for long-term intravital microscopic imaging & sample tracking (Feedback-loop automatic stage control) • T motion compensation: Image-based image XY position adjustment for long-term intravital microscopic imaging & sample tracking (Feedback-loop automatic stage control) • Combination of above three compensation for 4D <i>in vivo</i> motion compensation • Controllable by IVM Engine software
Accessories Add-on	Live Animal Maintenance Unit	• Body Temp. Monitoring & Feedback Heater Control, including tablet PC • 4CH Rectal Probe, Body Plate Heater, Thermometer Sensor & Cover Glass Heater
	<i>In vivo</i> Imaging Chamber Sets	• Dorsal Skinfold Chamber • Lung Imaging Chamber • Cranial Imaging Window • Abdominal Imaging Window • Pancreas Imaging Window • Mammary Imaging Window • Heart Imaging Chamber • Uterus Imaging Chamber
	Inhalation Anesthesia System	• Whole Rodent Animal Inhalation Anesthesia System • Anesthesia Mask and Connections for Longitudinal Imaging
	Antibodies / Dyes	• Fluorescent labeling agents, vascular dyes and conjugated antibodies
Engine & Studio Software	Image Display	• Independent 4 single channel display (RGBA channel) • Overlay channel display (Selection among RGBA channel)
	<i>In vivo</i> Imaging Modes	• Mosaic imaging (XY), Z-stack imaging (Z), Time-lapse imaging (T) • Time-lapse imaging at Multi-position (T - M) • Time-lapse & Z-stack imaging (TZ) • Time-lapse & Z-stack imaging at Multi-position (TZ - M)

### New All-in-One IVM Series Size Information



**IVM Technology, Inc.**

**Webpage**  
www.ivimtech.com

**Contact**  
information@ivimtech.com

**TEL** +82-2-431-7450

**FAX** +82-2-3400-0450